#### **CLAIMS**

1. A device comprising:

a motor having a frame of which surface is conductive;

a grounding terminal disposed at a place facing the frame;

and

an elastic member made of conductive resin and disposed between the frame and said grounding terminal.

10

15

25

### 2. A device comprising:

- (a) a motor having a frame of which surface is conductive and a motor terminal shaping in a leaf spring;
- (b) a feeding terminal for powering said motor and disposed at a place facing the motor terminal;
- (c) a grounding terminal disposed at a place facing the frame;
- (d) a first elastic member made of insulating resin and disposed for urging the motor terminal to said feeding terminal; and
- (e) a second elastic member made of conductive resin and disposed between the frame and said grounding terminal.

## 3. A device comprising:

- (a) a motor having a frame of which surface is conductive, a first motor terminal and a second motor terminal both shaping in leaf springs;
  - (b) a first feeding terminal for powering said motor and disposed at a place facing the first motor terminal;

(c) a second feeding terminal for powering said motor and disposed at a place facing the second motor terminal;

(d) a first elastic member made of insulating resin and disposed for urging the first motor terminal to said first feeding terminal; and

(e) a second elastic member made of conductive resin, disposed between the frame and said second feeding terminal, and disposed

for urging the second motor terminal to said second feeding terminal.

10 5 W Z

5

4. The device as defined in Claim 1 further comprising:

a housing; and

a board having said grounding terminal,

wherein said motor and said elastic member are sandwiched between said housing and said board.

15

20

5. The device as defined in Claim 2 further comprising:

a housing; and

a board having said feeding terminal and said grounding

wherein said motor, said first and said second elastic members are sandwiched between said housing and said board.

- 6. The device as defined in Claim 3 further comprising:
  - a housing;
  - a board including said first and said second feeding
- 25 terminals,

wherein said motor, said first and said second elastic members are sandwiched between said housing and said board.

10

15

- 7. The device as defined in Claim 2, wherein said first and second elastic members are unitarily formed by two-color-molding method.
- 5 8. The device as defined in Claim 3, wherein said first and second elastic members are unitarily formed by two-color-molding method.
  - 9. The device as defined in Claim 1, wherein said elastic member is synthetic rubber.
  - 10. The device as defined in Claim 2, wherein said first and said second elastic members are synthetic rubber.
  - 11. The device as defined in Claim 3, wherein said first and said second elastic members are synthetic rubber.
  - 12. The device as defined in Claim 1, wherein the frame roughly shapes in a cup, and an opening of the cup is covered by said elastic member.
- 20 13. The device as defined in Claim 2, wherein the frame roughly shapes in a cup, and an opening of the cup is covered by said second elastic member.
- 14. The device as defined in Claim 3, wherein the frame roughly shapes in a cup, and an opening of the cup is covered by said second elastic member.

10

15

25

- 15. The device as defined in Claim 4 further comprising a radio transceiver mounted to said board.
- 16. The device as defined in Claim 5 further comprising a radio transceiver mounted to said board.
  - 17. The device as defined in Claim 6 further comprising a radio transceiver mounted to said board.
  - 18. The device as defined in Claim 1, wherein said motor includes an unbalance mechanism for generating a vibration due to rotating.
  - 19. The device as defined in Claim 2, wherein said motor includes an unbalance mechanism for generating a vibration due to rotating.
  - 20. The device as defined in Claim 3, wherein said motor includes an unbalance mechanism for generating a vibration due to rotating.
  - 21. A motor including a frame having a conductive surface,
    wherein said frame is conductive to a grounding terminal of a device via an
    elastic member made of conductive resin.

# 22. A motor comprising:

a frame of which surface is conductive; and a motor terminal shaping in a leaf spring,

wherein said motor terminal is urged by a first elastic member made of insulating resin to a feeding terminal of a device, and said frame is conductive to a grounding terminal of the device via a second elastic member made of conductive resin.

# 23. A motor comprising:

5 a frame of which surface is conductive; and

a first and a second motor terminals both shaping in leaf springs;

wherein said first motor terminal is urged by a first elastic member made of insulating resin to a first feeding terminal of a device,

said second motor terminal is urged by a second elastic member made of conductive resin to a second feeding terminal of the device, and

said frame is conductive to said second motor terminal via the second elastic member.

15

10